



特性		Characteristic		
1.01	型号	Model		RTD30
1.02	动力形式	Power Type		柴油 Diesel
1.03	额定起重量	Rated Capacity	kg	3000
1.04	载荷中心距	Load Center	mm	600
尺寸参数		Dimension Parameter		
2.01	起升高度	Lift Height	H	mm 3000
2.02	货叉尺寸	Fork Size(L×W×T)	↓,3	mm 1220×125×45
2.03	门架倾角(前/后)	Mast Tilt Angle(F/R)	α/β	Deg 10°/12°
2.04	全长(不带货叉)	Overall Length(without Forks)	L	mm 3060
2.05	全宽	Overall Width	W	mm 1604
2.06	门架高度	Mast Lowered Height	H1	mm 2115
2.07	货叉最大起升高度	Mast Extended Height	H2	mm 4250
2.08	护顶架高度	Overhead Guard Height	H3	mm 2200
2.09	前悬距	Front Overhang	L1	mm 601
2.10	最小离地间隙(空载/满载)	Ground Clearance(Bottom of mast)	H4	mm 265/250
2.11	最小转弯半径	Turning Radius(outside)	r	mm 2750
2.12	最小直角通道宽度	Min.insecting aisle	Ast	mm 2615
2.13	轴距	Wheelbase	L2	mm 1835
2.14	自重	Service Weight	kg	4800
性能参数		Performance Parameter		
3.01	行驶速度(空载/满载)	Travel(Unloaded/Loaded)	Km/h	22/22
3.02	起升速度(空载/满载)	Lifting(Unloaded/Loaded)	mm/s	480/450
3.03	下降速度(空载/满载)	Lowng(Unloaded/Loaded)	mm/s	400/500
3.04	最大爬坡度	Max.Gradeability	%	16
轮胎		Tire		
4.01	前轮	Front		14-17.5-14PR
4.02	后轮	Rear		27×10-12-12PR
驱动、传动控制装置		Engine and Gearbox		
5.01	蓄电池(电压/容量)	Battery(Voltage/Capacity)	V/Ah	12/90
5.02	发动机型号	Engine Model		4TNE98-BQFLC
5.03	制造商	Manufacturer		YANMAR
5.04	额定输出功率/转速	Rated output/r.p.m.	kW	42.1/2300
5.05	额定扭矩/转速	Rated torque/r.p.m.	N·m	186-206/1700
5.06	汽缸数量	No.of Cylinder		4
5.07	缸径×行程	Bore×Stroke	mm	98×110
5.08	燃油箱容积	Fuel Tank Capacity	L	60
5.09	变速箱型号	Transmission Model		Automatic
5.10	传动方式	Drive Type		2WD

